

GENERAL**WARNING**

FATO located on water. Only for emergency landing. MLW 6T. Use TLOF on land for parking.

Operational hours

AD OPS Hours H24, PPR 15 min

Airport information

Note. AIP ESSB: Outside ATS hours of operation intentions should be transmitted on freq. 118:105 when flying over Stockholm city.

Ambulance and rescue flights only!

PPR 15 min H24 Rescue Coordination Center (SOS Alarm) PN H24 Centre +46 (0)8 454 26 22 or via RAKEL.

Clear to land when lights are on or radio contact.

Airport lightning can be lit up by Rakel Status 39135 MSISDN and extinguished Status: 39136 MSISDN or lit up by sending on freq. 122.875, 1 long- 7 sec, + 4 short within 1,8 sec.

Emergency reception + 46 8 123 55 671

Communication

RAKEL 330-3432

Clearance

Clearance from ESSB TWR requested when operational

Heliport information

ESHD							
	POS TLOF LAT 59 23 27N/ LONG 018 02 00E(*)						
	POS FATO LAT 59 23 29N / LONG 018 01 48E(*)						
Dimensions: Max RD 11.94m D value max 13.73 m MLW 6 ton	AD TLOF ELEV 5 ft./ FATO ELEV 5 ft. TLOF Ø 20 m Surface Asphalt FATO 19m x 19 m Surface wood floating/moored						
	SECTORS						
	<table border="1"> <thead> <tr> <th>APPROACH</th> <th>DEPARTURE</th> </tr> </thead> <tbody> <tr> <td>W (west) 4,5% 092°TH</td> <td>4,5 % 272°TH</td> </tr> <tr> <td>S (South) 4,5% 287° TH CURVED</td> <td>4,5% 107° TH CURVED</td> </tr> </tbody> </table>	APPROACH	DEPARTURE	W (west) 4,5% 092°TH	4,5 % 272°TH	S (South) 4,5% 287° TH CURVED	4,5% 107° TH CURVED
APPROACH	DEPARTURE						
W (west) 4,5% 092°TH	4,5 % 272°TH						
S (South) 4,5% 287° TH CURVED	4,5% 107° TH CURVED						
RFF 2 hose spray 4 Fire Extinguishers 12 kg	Lights: TLOF 16 green perimeter lights + 2 floodlights FATO 12 white perimeter lights Lighted Windsock						

