

GENERAL WARNING

FATO/TLOF is only designed for one helicopter at a time

TSFS 2012:79 6 § Anläggningsbestämmelserna i dessa föreskrifter bygger på antagandet att endast en helikopter i taget befinner sig inom FATO/TLOF

Operational hours

AD OPS H24, PPR 15 min

Airport information

Ambulance and rescuer flights only

PPR 15 min H24 Rescue Coordination Center (SOSAB) PN H24 +46 8 454 26 22.

Heliport free/ready to land when lights are on or radio contact. See AIP for more info.

Switchboard +46(0)8 123 55 000

ALTN: ESHK twin FATO/TLOF, ESHC, ESHL, ESSB.

Communication

Contact Bromma TWR (ESSB) 118.105 for clearance prior entry in CTR and prior takeoff

AIP ESSB: "Outside ATS hours of operation intensions should be transmitted on frequency 118.105 when flying over Stockholm city".

Rakel 330-3432 Heliport

Clearance

Request clearance from ESSB TWR when operational/ open.

Heliport information

ESHD													
Elevated on 13 floor level	POS LAT 59° 23' 28.67"N LONG 0 18° 02' 16.19" E												
Proportion/dimension for MAX RD 16,36 m D value max 20 m MLW 11 ton 220V available. 400V available.	AD ELEV 216 ft. FATO/TLOF 20x20 m Surface Concrete Magnetic var 7° E 2024-2029 <table border="1"> <thead> <tr> <th colspan="2">SECTORS</th></tr> <tr> <th>APPROACH</th><th>DEPARTURE</th></tr> </thead> <tbody> <tr> <td>NW 4,5% 161° GEO/ 154° MAG</td><td>NW 4,5% 341° GEO/ 334° MAG</td></tr> <tr> <td>NE 4.5% 213° GEO/ 206° MAG</td><td>NE 4,5% 033° GEO/ 026° MAG</td></tr> <tr> <td>SE 4,5 % 341° GEO/ 334° MAG</td><td>SE4,5 % 161° GEO/ 154° MAG</td></tr> <tr> <td>SW 4,5% 058° GEO/ 051° MAG</td><td>SW 4,5% 238° GEO/ 231°MAG</td></tr> </tbody> </table>	SECTORS		APPROACH	DEPARTURE	NW 4,5% 161° GEO/ 154° MAG	NW 4,5% 341° GEO/ 334° MAG	NE 4.5% 213° GEO/ 206° MAG	NE 4,5% 033° GEO/ 026° MAG	SE 4,5 % 341° GEO/ 334° MAG	SE4,5 % 161° GEO/ 154° MAG	SW 4,5% 058° GEO/ 051° MAG	SW 4,5% 238° GEO/ 231°MAG
SECTORS													
APPROACH	DEPARTURE												
NW 4,5% 161° GEO/ 154° MAG	NW 4,5% 341° GEO/ 334° MAG												
NE 4.5% 213° GEO/ 206° MAG	NE 4,5% 033° GEO/ 026° MAG												
SE 4,5 % 341° GEO/ 334° MAG	SE4,5 % 161° GEO/ 154° MAG												
SW 4,5% 058° GEO/ 051° MAG	SW 4,5% 238° GEO/ 231°MAG												
RFF Class H3 16-20 m, 12 fixed foam spay nozzles/ 2 x750 liter foam. 1 manual hose spray lines 50 m. Fire Extinguisher: 50 kg carbon dioxide, 50 kg powder, 50 l foam.	Lights: Airport flash Perimeter light green 28 Floodlights 4 Lightning Windsock												





